

## 2 Bolt Anchor Replacement/Relocation Application

August 24th 2017

Redgarden Wall, South Buttress

Desdicahdo 5.13c

FFA Christian Griffith

**Purpose of application:** To move the current anchor down ~20 feet. Currently the anchor is comprised of two pins, one ring bolt, and a rotten sling. There is no way to lower off without leaving your own gear. The anchor is set back on a slab in a way that creates a lot of drag. So much drag that you are almost left helpless if you lower.

### Information from FHRC

#### Factors

**1. Does the proposed fixed hardware relocation alter the route technical difficulty?**

No. You would clip the new anchor well after the hard climbing. The climbing up to the old anchor from the proposed anchor is an easy slab.

**2. Does the proposed fixed hardware relocation alter the route psychology?**

No. Most parties lower off from the last bolt and do not go up to the current anchor.

**3. Does the proposed fixed hardware relocation alter neighboring routes?**

No.

**4. Does the FFA party (Christian Griffith) agree with the proposed fixed hardware relocations?**

No. Christian does not want the anchor moved. He believes it is a convenience anchor and it will create an eye sore for the canyon.

#### Factors Against

None

#### Neutral Factors

The new anchor will help facilitate the replacement of the 4 lead bolts.

Current anchor with proposed bolt locations of the new anchor

